



Vincotech

30-P2126PA150SH01-L280F14Y

target datasheet

flowPACK 2

1200 V / 150 A

Topology features

- 3xHalf Bridge
- Open Emitter configuration
- Kelvin Emitter for improved switching performance
- Temperature sensor

Component features

- Easy paralleling
- High speed switching
- Low switching losses

Housing features

- Base isolation: Al₂O₃
- Convex shaped baseplate for superior thermal contact
- Cu baseplate
- Thermo-mechanical push-and-pull force relief
- Press-fit pin
- Reliable cold welding connection

Target applications

- Elevator Drives
- Embedded Drives
- Industrial Drives


Types

- 30-P2126PA150SH01-L280F14Y

flow 2 17 mm housing



Schematic





Vincotech

30-P2126PA150SH01-L280F14Y
target datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	200	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	450	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	374	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	118	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	900	A
Surge current capability	I^2t		4050	A^2s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	237	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Module Properties

Thermal Properties

Storage temperature	T_{stg}		$-40\dots+125$	$^{\circ}\text{C}$
Operation temperature under switching condition	T_{jop}		$-40\dots+(T_{jmax} - 25)$	$^{\circ}\text{C}$

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage $t_p = 2\text{ s}$	6000	V
Creepage distance			$>12,7$	mm
Clearance			$>12,7$	mm
Comparative Tracking Index	CTI		≥ 200	



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0052	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	V_{CEsat}		15		150	25	1,78	2,05	2,42	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			2	µA
Gate-emitter leakage current	I_{GES}		20	0		25			240	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	25		25		8800		pF
Reverse transfer capacitance	C_{res}							470		pF
Gate charge	Q_g		15		0	25		1140		nC

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,25		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Inverter Diode

Static

Forward voltage	V_F				150	25 150		2,14 2,07	2,46 2,38	V
Reverse leakage current	I_R	$V_r = 1200 \text{ V}$				25 150		14000	180 28000	µA

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,4		K/W
-------------------------------------	---------------	---	--	--	--	--	--	-----	--	-----



Vincotech

30-P2126PA150SH01-L280F14Y
target datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Thermistor

Static

Rated resistance	R					25		22		k Ω
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 1484 \Omega$				100	-5		5	%
Power dissipation	P					25		130		mW
Power dissipation constant	d					25		1,5		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 1 \%$						3962		K
B-value	$B_{(25/100)}$	Tol. $\pm 1 \%$						4000		K
Vincotech Thermistor Reference									I	



Vincotech


30-P2126PA150SH01-L280F14Y

target datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	30-P2126PA150SH01-L280F14Y
With thermal paste (5,2 W/mK, PTM6000HV)	30-P2126PA150SH01-L280F14Y-/-/7/
With thermal paste (3,4 W/mK, PSX-P7)	30-P2126PA150SH01-L280F14Y-/-3/

Marking						
	Text	Name	Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTTIVV	WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver	Lot number	Serial	Date code	
		TTTTTIVV	LLLLL	SSSS	WWYY	

Outline							
Pin table [mm]							
Pin	X	Y	Function	26	54,5	5,4	DC-3
1	0,9	0	S11	27	57,2	0	DC-3
2	0,9	3	G11	28	65,8	0	DC+3
3	3,9	0	DC-1	29	65,8	2,7	DC+3
4	3,9	2,7	DC-1	30	68,5	0	DC+3
5	3,9	5,4	DC-1	31	68,5	2,7	DC+3
6	6,6	0	DC-1	32	64,7	36	G16
7	15,2	0	DC+1	33	61,7	36	S16
8	15,2	2,7	DC+1	34	58,7	36	PH3
9	17,9	0	DC+1	35	56	36	PH3
10	17,9	2,7	DC+1	36	53,3	36	PH3
11	26,2	0	S13	37	50,6	36	PH3
12	26,2	3	G13	38	39,4	36	G14
13	29,2	0	DC-2	39	36,4	36	S14
14	29,2	2,7	DC-2	40	33,4	36	PH2
15	29,2	5,4	DC-2	41	30,7	36	PH2
16	31,9	0	DC-2	42	28	36	PH2
17	32,2	4,05	NTC	43	25,3	36	PH2
18	40,5	0	DC+2	44	14,1	36	G12
19	40,5	2,7	DC+2	45	11,1	36	S12
20	43,2	0	DC+2	46	8,1	36	PH1
21	43,2	2,7	DC+2	47	5,4	36	PH1
22	51,5	0	S15	48	2,7	36	PH1
23	51,5	3	G15	49	0	36	PH1
24	54,5	0	DC-3				
25	54,5	2,7	DC-3				




Outline drawing of the component



Vincotech

30-P2126PA150SH01-L280F14Y
target datasheet



Identification					
ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	150 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	150 A	Inverter Diode	
Rt	NTC			Thermistor	



Vincotech

30-P2126PA150SH01-L280F14Y
target datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 36	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow 2</i> packages see vincotech.com website.

Package data
Package data for <i>flow 2</i> packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,op}=175^{\circ}\text{C}$ and up to 3500VAC/1min isolation voltage. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
30-P2126PA150SH01-L280F14Y-T1-14	28 Jul. 2026	Initial Release	

Product status definition		
Datasheet Status	Product Status	Definition
Target	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. The data contained is exclusively intended for technically trained staff.

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.