



Vincotech

A0-VP12PMA075RA-LF16A80T

datasheet

VINcoPIM E3

1200 V / 75 A

Topology features

- Common Emitter configuration
- Converter+Brake+Inverter
- Temperature sensor

Component features

- Easy paralleling
- Low collector emitter saturation voltage
- Low turn-off losses

Housing features

- Base isolation: IMB
- SoLid Cover Technology
- Standard mid-power industry package
- Available with press-fit and solder-pin
- Reliable cold welding connection to PCB
- Press-fit terminals


Target applications

- Elevator Drives
- General Purpose Drives
- Industrial Drives
- Servo Drives


Types

- A0-VP12PMA075RA-LF16A80T

VINco E3 17 mm housing



Schematic





Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inverter Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	115	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	225	A
Turn off safe operating area		$T_j = 150\text{ °C}$, $V_{CE} = 1200\text{ V}$	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	240	W
Gate-emitter voltage	V_{GES}		± 30	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	8	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Inverter Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	84	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	182	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Brake Switch

Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	76	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	150	A
Turn off safe operating area		$T_j = 150\text{ °C}$, $V_{CE} = 1200\text{ V}$	150	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	173	W
Gate-emitter voltage	V_{GES}		± 30	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	8	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Brake Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	41	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	75	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	89	W
Maximum junction temperature	T_{jmax}		175	°C

Rectifier Diode

Peak repetitive reverse voltage	V_{RRM}		1600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	148	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	600	A
Surge current capability	I^2t		1800	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	200	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Creepage distance			>12,7	mm
Clearance			9	mm
Comparative Tracking Index	CTI		≥ 200	

*100 % tested in production



Vincotech

A0-VP12PMA075RA-LF16A80T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			5	0,0093	25	5,5	6,3	7,1	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		75	25 125 150		1,45 1,62 1,66	1,95 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			10	µA
Gate-emitter leakage current	I_{GES}		30	0		25			500	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	30		25		12541		pF
Output capacitance	C_{oes}							285		pF
Reverse transfer capacitance	C_{res}							104		pF
Gate charge	Q_g		0/15	600	75	25		456		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2 \text{ W/mK}$ (PTM)						0,4		K/W
--	---------------	---	--	--	--	--	--	-----	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 8 \Omega$ $R_{goff} = 8 \Omega$	± 15	600	75	25 125 150		239,9 240,01 240,11		ns
Rise time	t_r					25 125 150		35,02 42,88 44,29		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		227,56 261,66 271,86		ns
Fall time	t_f					25 125 150		128,63 179,07 191,31		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 5,04 \mu C$ $Q_{tFWD} = 9,95 \mu C$ $Q_{tFWD} = 11,87 \mu C$				25 125 150		5,01 7,7 8,64		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		6,44 9,26 10,18		mWs



Vincotech

A0-VP12PMA075RA-LF16A80T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inverter Diode

Static

Forward voltage	V_F				75	25 125 150		1,71 1,95 1,97	2,1 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25			10	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,52		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=2324$ A/µs $di/dt=1879$ A/µs $di/dt=1803$ A/µs	± 15	600	75	25 125 150		72,94 73,53 74,64		A
Reverse recovery time	t_{rr}					25 125 150		212,5 414,9 475,71		ns
Recovered charge	Q_r					25 125 150		5,04 9,95 11,87		µC
Reverse recovered energy	E_{rec}					25 125 150		1,72 3,76 4,53		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		1892,83 986,66 767,04		A/µs



Vincotech

A0-VP12PMA075RA-LF16A80T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Brake Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$			5	0,0059	25	5,5	6,3	7,1	V
Collector-emitter saturation voltage	V_{CEsat}		15		50	25 125 150		1,49 1,72 1,79	1,95 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			10	µA
Gate-emitter leakage current	I_{GES}		30	0		25			500	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 1 \text{ Mhz}$	0	30	25			8530		pF
Output capacitance	C_{oes}							193		pF
Reverse transfer capacitance	C_{res}							67		pF
Gate charge	Q_g		0/15	600	100	25		319		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2 \text{ W/mK}$ (PTM)						0,55		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 16 \Omega$ $R_{goff} = 16 \Omega$	0/15	700	25	25 125 150		103,61 100,64 98,6		ns
Rise time	t_r					25 125 150		24,94 29,14 31,36		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		584,52 652,17 671,49		ns
Fall time	t_f					25 125 150		179,16 232,22 248,5		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD}=1,21 \mu C$ $Q_{tFWD}=3,4 \mu C$ $Q_{tFWD}=4,02 \mu C$				25 125 150		1,84 2,56 2,79		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		3,12 4,37 4,74		mWs



Vincotech

A0-VP12PMA075RA-LF16A80T

datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Brake Diode

Static

Forward voltage	V_F				25	25 125 150		1,84 1,69 1,69	2,1 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 1200$ V				25			10	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						1,07		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=1188$ A/μs $di/dt=922$ A/μs $di/dt=780$ A/μs	0/15	700	25	25 125 150		29,55 28,35 29,1		A
Reverse recovery time	t_{rr}					25 125 150		64,65 334,45 384,49		ns
Recovered charge	Q_r					25 125 150		1,21 3,4 4,02		μC
Reverse recovered energy	E_{rec}					25 125 150		0,263 1,5 1,81		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		344,72 276,12 230,34		A/μs



Vincotech

A0-VP12PMA075RA-LF16A80T

datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Rectifier Diode

Static

Forward voltage	V_F				50	25 125 150		1,06 0,984 0,964	1,5 ⁽¹⁾		V
Reverse leakage current	I_R	$V_r = 1600$ V				25 150			50 1500		µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 5,2$ W/mK (PTM)						0,47			K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	--	-----

Thermistor

Static

Rated resistance	R					25		5			kΩ
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 493$ Ω				100	-5		5		%
Power dissipation	P							245			mW
Power dissipation constant	d					25		1,4			mW/K
B-value	$B_{(25/50)}$	Tol. ±2 %						3375			K
B-value	$B_{(25/100)}$	Tol. ±2 %						3437			K
Vincotech Thermistor Reference									K		

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

A0-VP12PMA075RA-LF16A80T


datasheet

Inverter Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 19 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,396 K/W$
IGBT thermal model values

R (K/W)	τ (s)
9,95E-03	1,52E+01
8,67E-02	1,13E+00
1,82E-01	1,09E-01
9,19E-02	2,01E-02
2,84E-02	5,83E-04



Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet


Inverter Switch Characteristics

figure 5.

IGBT

Safe operating area

$I_C = f(V_{CE})$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$

$V_{GE} = 15 \text{ V}$

$T_j = T_{jmax}$



Vincotech

Inverter Diode Characteristics

figure 6.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$





Vincotech

A0-VP12PMA075RA-LF16A80T


datasheet

Brake Switch Characteristics

figure 8. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 9. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 10. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 9 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 11. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,548 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
1,74E-02	8,46E+00
1,01E-01	8,36E-01
2,64E-01	8,52E-02
1,26E-01	1,67E-02
4,30E-02	6,02E-04



Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet


Brake Switch Characteristics

figure 12.

IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D = \text{single pulse}$

$T_s = 80 \text{ } ^\circ\text{C}$

$V_{GE} = 15 \text{ V}$

$T_j = T_{jmax}$



Vincotech

Brake Diode Characteristics

figure 13. FWD





figure 14. FWD





Vincotech

Rectifier Diode Characteristics

figure 15.

Rectifier

Typical forward characteristics

$$I_F = f(V_F)$$





figure 16.

Rectifier

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$





Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet


Thermistor Characteristics

figure 17.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

A0-VP12PMA075RA-LF16A80T datasheet


Inverter Switching Characteristics

figure 18.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω


T_j : 25 °C
125 °C
150 °C

figure 20.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j : 25 °C
125 °C
150 °C

figure 19.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 75$ A


T_j : 25 °C
125 °C
150 °C

figure 21.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 75$ A

T_j : 25 °C
125 °C
150 °C



Vincotech

A0-VP12PMA075RA-LF16A80T datasheet


Inverter Switching Characteristics

figure 22.

IGBT

Typical switching times as a function of collector current

$$t = f(I_c)$$



With an inductive load at


$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω

figure 23.

IGBT

Typical switching times as a function of IGBT turn on gate resistor

$$t = f(R_g)$$



With an inductive load at


$T_j = 150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 75$ A

figure 24.

FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 25.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 75$ A

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

A0-VP12PMA075RA-LF16A80T datasheet


Inverter Switching Characteristics

figure 26.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j : 25 °C
125 °C
150 °C

figure 28.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω


T_j : 25 °C
125 °C
150 °C

figure 27.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 75$ A


T_j : 25 °C
125 °C
150 °C

figure 29.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_c = 75$ A

T_j : 25 °C
125 °C
150 °C




Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet

Inverter Switching Characteristics

figure 30. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 8$ Ω

T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 31. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at


$V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $I_C = 75$ A

T_j : 25 °C (blue), 125 °C (black), 150 °C (red)

figure 32. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 8$ Ω
 $R_{goff} = 8$ Ω



Vincotech

A0-VP12PMA075RA-LF16A80T datasheet


Brake Switching Characteristics

figure 33.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_c)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω


T_j : 25 °C
125 °C
150 °C

figure 35.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_c)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 16$ Ω


T_j : 25 °C
125 °C
150 °C

figure 34.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_c = 25$ A


T_j : 25 °C
125 °C
150 °C

figure 36.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_c = 25$ A

T_j : 25 °C
125 °C
150 °C



Vincotech


A0-VP12PMA075RA-LF16A80T
datasheet

Brake Switching Characteristics

figure 37.

IGBT

Typical switching times as a function of collector current
 $t = f(I_C)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω

figure 38.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_C = 25$ A

figure 39.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_C)$



With an inductive load at


$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 16$ Ω

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 40.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_C = 25$ A

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

A0-VP12PMA075RA-LF16A80T datasheet


Brake Switching Characteristics

figure 41.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 16$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 43.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 16$ Ω


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 42.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_c = 25$ A


T_j :
— 25 °C
— 125 °C
— 150 °C

figure 44.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_c = 25$ A

T_j :
— 25 °C
— 125 °C
— 150 °C




Vincotech

A0-VP12PMA075RA-LF16A80T datasheet

Brake Switching Characteristics

figure 45. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$



With an inductive load at


$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $R_{gon} = 16$ Ω

T_j :
— 25 °C
— 125 °C
— 150 °C

figure 47. IGBT

Reverse bias safe operating area


$I_C = f(V_{CE})$



At $T_j = 150$ °C
 $R_{gon} = 16$ Ω
 $R_{goff} = 16$ Ω

figure 46. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = 0/15$ V
 $I_C = 25$ A

T_j :
— 25 °C
— 125 °C
— 150 °C



Vincotech

A0-VP12PMA075RA-LF16A80T datasheet

Switching Definitions

figure 48. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 49. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 50. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 51. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

A0-VP12PMA075RA-LF16A80T

datasheet

Switching Definitions

figure 52. FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 53. FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





A0-VP12PMA075RA-LF16A80T


datasheet

Vincotech

Ordering Code	
Version	Ordering Code
Without thermal paste	A0-VP12PMA075RA-LF16A80T
With thermal paste (5,2 W/mK, PTM6000HV)	A0-VP12PMA075RA-LF16A80T-/7/

Marking						
	Text	Name	VIN	Date code	Lot	Serial
		NN-NNNNNNNNNNNNNN- TTTTT	VIN	WWYY	LLLLL	SSSS
	Datamatrix	Type&Ver TTTTTTVV	Lot number LLLLL	Serial SSSS	Date code WWYY	

Outline			
Pin table [mm]			
Pin	X	Y	Function
1	19,05	0	ACIn1
2	22,86	0	ACIn1
3	34,29	0	ACIn2
4	38,1	0	ACIn2
5	49,53	0	ACIn3
6	53,34	0	ACIn3
7	64,77	0	G12
8	68,58	0	Ph1
9	72,36	0	Ph1
10	83,82	0	G14
11	87,56	0	Ph2
12	91,45	0	Ph2
13	118,11	15,865	G16
14	118,11	19,675	Ph3
15	118,11	23,485	Ph3
16	118,11	34,915	Therm1
17	118,11	38,725	Therm2
18	100,965	58,4	G15
19	97,155	58,4	S
20	93,305	58,4	G13
21	70,505	58,4	S
22	66,655	58,4	G11
23	62,855	58,4	G27
24	51,395	58,4	DC-Inv
25	47,585	58,4	DC-Inv
26	36,195	58,4	DC+Inv
27	32,385	58,4	DC+Inv
28	20,975	58,4	Br
29	17,175	58,4	Br
30	0	42,535	DC+Rect
31	0	38,725	DC+Rect
32	0	34,915	DC+Rect
33	0	23,485	DC+Rect
34	0	19,675	DC+Rect
35	0	15,865	DC+Rect






Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
T11, T12, T13, T14, T15, T16	IGBT	1200 V	75 A	Inverter Switch	
D11, D12, D13, D14, D15, D16	FWD	1200 V	75 A	Inverter Diode	
T27	IGBT	1200 V	50 A	Brake Switch	
D27	FWD	1200 V	25 A	Brake Diode	
D31, D32, D33, D34, D35, D36	Rectifier	1600 V	50 A	Rectifier Diode	
Rt	Thermistor			Thermistor	



Vincotech

A0-VP12PMA075RA-LF16A80T
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 24	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for VINco E3s packages see vincotech.com website.

Package data
Package data for VINco E3s packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,sp}=150^{\circ}\text{C}$ and up to 2500VAC/1min isolation voltage. For more information see vincotech.com website.



Document No.:	Date:	Modification:	Pages
A0-VP12PMA075RA-LF16A80T-D2-14	29 Sep. 2026	Add UL listing	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.